

Project #:	





This microwave oven is ideal for...

Applications

- Convenience Stores
- Coffee shops
- Dessert stations
- Teachers/Staff lounge
- Nurses stations
- Vending

Boost heats and re-therms foods in seconds

- Slice of apple pie re-therms in 20 seconds
- 9 oz. (255g) cup of chili re-therms in 1:45

Commercial Microwave Ovens

Culitek CTMS10TS & CTMS10DS Models

Power Output

- 1000 watts of power
- Perfect replacement for inappropriate domestic ovens used in foodservice applications

Available with Touch or Dial Controls

- Touch controls:
 - 20 programmable menu items simplifies cooking
 - 5 power levels and 4 cooking stages for cooking flexibility
 - Multiple quantity pad calculates the proper cooking times for multiple portions
- Dial Controls:
 - Timer automatically resets to zero if door is opened during heating
 - 6 minute digital timer lights up for "at-a-glance" monitoring
 - Full power only for simple operation

Easy to Use

- See-through door and lighted interior for monitoring without opening the door
- 0.8 cubic foot (23 liter) capacity accommodates a 12" (305mm) platter, prepackaged foods and single servings

Certified Oven for Commercial Applications

- Tested to higher standards for a commercial rating —required by most commercial insurance polices and health inspectors
- Interlock safety switch is tested to 4 times the standard of residential ovens
- Constructed to withstand the foodservice environment, multiple users and variable ambient temperatures
- Compared to a residential oven, this oven is more powerful for faster heating and better quality results
- Engineered for a simple, "self-service" operation

Easy to Maintain

- · Stainless steel exterior wrap, door, and oven interior for increased durability
- · Sealed-in Borosilicate Glass shelf for easy cleaning

Service

All products are backed by Culitek Commercial Service

CULITEK

Commercial Service 800-436-9472

Warranty

Warranty Certificate for this product can be found on the Culitek. website at <u>culitekequipment.com</u>

Safety and Sanitation

This product meets and exceeds safety and sanitation standards set for commercial microwave ovens by UL, ETL, NSF, CSA, and FDA









Dimensions								
Exterior	H 1	2 1/4" (310)	W 20 1/8" (512)		D† 15 %" (403)			
Cavity	H 7	3/4" (197)	W 13" (330)		D 13" (330)			
Usable Cavity Space	0.8 cubic ft. (23 liter)							
Door Depth	29"	29" (738), 90°+ door open						
Installation Clearances	Top	: 7" (177.8)	Sides: 1" (25)		Back: None			
Shipping Carton	H 1	5" (381)	W 23" (584)		D 18" (457)			
Weight								
Product Weight	Ship weight (approx.)			UPS Shippable				
30 lbs. (13.6 kg.)		37 lbs. (16.8 kg.)		Yes				

 ${\it Measurements \ are \ US \ Standard. \ Measurements \ in \ (\) \ are \ in \ millimeters}$

* IEC 60705 Tested

† Includes handle

Features					
	Touch Models (TS)	DIal Models (DS)			
Configuration	Countertop	Countertop			
Stackable	No	No			
Display	LED	Lighted Dial			
Control System	Touchpad	Dial			
Programmable Control	Yes, 10 pads	No			
Braille	No	No			
Settings Programmable	20	-			
Max. Cooking Time	30:00	6:00			
Microwave Distribution	Rotating stirrer, bottom	Rotating stirrer, bottom			
Power Levels	5	1			
Defrost	Yes, 20% power	No			
Time Entry Option	Yes	Yes			
Multiple Portion Setting	Yes, X2	No			
Stage Cooking	4 stages	1 stage			
Interior Light	Yes, LED	Yes, LED			
Automatic Voltage Sensor	No	No			
Air Filter	No	No			
Signal	End of cycle, adjustable	End of cycle			
Door Handle	Grab & Go	Grab & Go			
Exterior Finish	Stainless steel	Stainless steel			
Interior Finish	Stainless steel	Stainless steel			

Electrical Configuration									
Model#/ UPC	Control System	Power Consumption	Power Output (microwave)	Power Source	Plug Configuration	Cord Length	Frequency	Magnetron	
CTMS10TS 810081733663	Touch	1500 W, 13A	1000 W*	120 V, 60 Hz, 15 A, single phase	NEMA 5-15	5 ft. (1.5m)	2450MHz	1	
CTMS10DS 810081733656	Dial	1500 W, 13A	1000 W*	120 V, 60 Hz, 15 A, single phase	NEMA 5-15	5 ft. (1.5m)	2450MHz	1	

